



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. High efficiency constant current driver, ensure the light source is maximum used. can be easily installed in any type of space, to create amazing light effects, The LED is set back to minimize glare. The main body is made of die-cast aluminum that guarantees optimum heat dissipation, with Premium aluminum reflectors with different sizes and high-quality light. The typical beam angle change by different color, chip size and chip position.

FIELDS OF APPLICATION:

Living spaces, villas, residential, offices, showrooms, hotels, restaurants, buildings, hospitals, shopping malls, supermarket,, convention centers, bathrooms, kitchens, outdoor commercial spaces, etc.


The ASTER Recessed ceiling luminaries adaptable for both indoor and outdoor applications.

High Lumen Efficacy 115 lm/W - UGR<19
 Body - Die cast aluminum housing with solvent free powder coating
 Reflector - Anodized aluminum
 Diffuser - polycarbonate pattern lens
 Glowing Wire Test - 850°
 Temperature - of=20 °C ~ of max=50 °C

ASTER-A-1-15-27-W-10W



Model --- **ASTER**



ASTER

Size	A - B - C - D									
Driver	1	2	3	4	5	6	7			
	On/Off	Dali	1-10	Phase Dimming	RGBW	Casambi	Tuya			
Beam Angle	15° - 24° - 36° - 60°									
Kelvin	27	30	40	50	60	TUN	1	2		
	2700k	3000k	4000k	5000k	6000k	Tunable	RGB	RGBW		
Finishing	W		B		S		X			
	white		black		silver		as per requested			
Wattage	10	14	18	20	24	30	35	40	45	50

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.


IP65 COB McA Step 3 220-240V



- A - Ø 110-60mm 95mm
- B - Ø 127-76mm 110mm
- C - Ø 165-82mm 145mm
- D - Ø 220-95mm 200mm


Relative spectral perception of brightness and melanopic effect

Effect as a percentage







Explanation of the three curves:
 S_w(A) = Perception of brightness, daytime seeing with the cones
 V(A) = Nighttime seeing with the rods
 S_m(A) = Melatonin suppression with the photosensitive ganglion cells

Wavelength (nm)



Available Accessories



LED life time		Operating time 1.000 h										
Lamp Lumen Maintenance Factor		1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor		1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.60
		LSF	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.80
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99



LED

AC220-240V

series wiring

