



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. High efficiency constant current driver, ensure the light source is maximum used. can be easily installed in any type of space, to create amazing light effects, The LED is set back to minimize glare. The main body is made of die-cast aluminum that guarantees optimum heat dissipation with single optic lens family in the most popular sizes and beams with excellent color rendering, and Supreme light quality.

FIELDS OF APPLICATION:

Living spaces, villas, residential, offices, showrooms, hotels, buildings, hospitals, shopping malls, supermarket, convention centers, galleries, etc.


The KONA Trimless ceiling luminaries adaptable for indoor applications.

High Lumen Efficacy 115 lm/W - UGR<19
 Body - Die cast aluminum housing with solvent free powder coating
 Diffuser - polycarbonate pattern lens
 Glowing Wire Test - 850°
 Temperature - of=20 °C ~ of max=50 °C

KONA-A-1-8-27-W-10W



Model --- **KONA**



KONA-SQ

Size	A		B						
Driver	1	2	3	4	5	6	7		
	On/Off	Dali	1-10	Phase Dimming	RGBW	Casambi	Tuya		
Beam Angle	8°		10°		15°		20°		
Kelvin	27	30	40	50	60	TUN	1	2	
	2700k	3000k	4000k	5000k	6000k	Tunable	RGB	RGBW	
Finishing	W		B		S		X		
	white		black		silver		as per requested		
Wattage	10		12		15		20	24	30

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

IP44 COB McA Step 3 220-240V




A - Ø 74-74-96mm 78-78mm

A - Ø 143-74-96mm 147-78mm

Relative spectral perception of brightness and melanopic effect

Effect as a percentage





Explanation of the three curves:
 S_m(A) = Perception of brightness, daytime seeing with the cones
 V(A) = Nighttime seeing with the rods
 S_m(A) = Melatonin suppression with the photosensitive ganglion cells

Die Attach
 Via Epoxy
 or Eutectic
 Solder



Available Accessories



LED life time

		Operating time 1.000 h										
Lamp Lumen Maintenance Factor		1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor		1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99



LED

AC220-240V

series wiring

