



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder, double anti-corrosion to extend service life. High efficiency constant current driver, ensure the light source is maximum used.

3000K, SIDE VIEW
 CRI: 90, 920LMS/M
 Led Qty: 120LEDS/M
 Length/Reel: 5M - 10M Working
 Temperature:- 20~50°C Storage
 Temperature: -30~80°C Voltage
 Range: 23 ~25V dc Reverse
 Voltage: : 25V dc

ST-LD-NEO-85043-14W-3K-1018-IP67





Model --- **NEO**



XXXX	Size	A						
	Driver	1	2	3	4	5	6	7
		On/Off	Dali	1-10	Phase Dimming	RGBW	Casambi	Tuya
	Kelvin	27	30	40	50	60	TUN	1
		2700k	3000k	4000k	5000k	6000k	Tunable	RGB
	Wattage/M	14.4						

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

IP67 SMD 24V 120LEDS 14.4W/M
 2835



DIMENSION

350mm(13.77")
 6mm (0.23") Wide
 5050mm(198.81") Max Run
 50mm(1.96") Cutting Length
 12mm (0.47") High

ALUMINUM PROFILE LIST

Product NO.	Section diagram	install
6x12mm		
6x12mm		

LED life time		Operating time 1,000 h										
Lamp Lumen Maintenance Factor	Lamp Survival Factor	1	10	20	30	40	50	60	70	80	90	100
L80	50,000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.60
		LSMF	1	1	1	1	1	1	0.99	0.99	0.99	0.98
L80	100,000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82
		LSMF	1	1	1	1	1	1	0.99	0.99	0.99	0.99



LED

AC220-240V

series wiring



LM-80

